

SAFETY DATA SHEET



Date of issue/Date of revision 30 June 2026

Version 1.04

Section 1. Identification

Product name : 96-2 PPG CUSTOM COLORANT CONCENTRATE B-LAMP BLACK
Product code : 00355821
Other means of identification : Not available.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Professional applications.
Use of the substance/ mixture : Pigment paste
Uses advised against : Not applicable.

Manufacturer : The Pittsburgh Paints Co.
500 Cranberry Woods Drive,
Cranberry Township, PA 16066
Emergency telephone number : 1-833-477-1553 (U.S. and Canada)
SETIQ Interior de la República: 800-00-214-00 (México)
Technical Phone Number : 1-800-441-9695 (U.S. and México)
1-800-387-2253 (Canada)

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture : ACUTE TOXICITY (oral) - Category 4
SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
CARCINOGENICITY - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 3.5% (oral), 54% (dermal), 79.9% (inhalation)

GHS label elements

Section 2. Hazards identification

Hazard pictograms

:

**Signal word**

: Danger

Hazard statements

: Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer.
May cause damage to organs through prolonged or repeated exposure. (kidneys)

Precautionary statements**Prevention**

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Storage

: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Contains isothiazolinones. May cause allergic reaction. Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.

Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification

: Not available.

Ingredient name	Synonyms	%	CAS number
Talc , not containing asbestiform fibres	Talc; magnesium silicate monohydrate (talc) not containing asbestiform fibres	≥15 - 40	14807-96-6
ethanediol	ethylene glycol; ethane-1,2-diol; 1,2-Ethanediol; Glycol; Monoethylene glycol; 1,2-Ethanediol (ethylene glycol); Glycol alcohol; 1,2-Dihydroxyethane; catalyst, containing N-(2-hydroxypropylammonium)diazabicyclo	≥10 - ≤30	107-21-1

Section 3. Composition/information on ingredients

carbon black	[2,2,2]octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol; 1,2-ethanediol Lampblack; Acetylene black; C.I. 77266; C.I. Pigment Black 6; C.I. Pigment Black 7; Charcoal	≥5 - ≤10	1333-86-4
Benzenesulfonic acid, dodecyl-, branched, compd. with 2-propanamine	Benzenesulfonic acid, dodecyl-, branched, compds. with 2-propanamine; fatty acids, montan-wax, mixed esters with adipic acid and trimethylolpropane; Dodecylbenzenesulfonic acid branched, compds. with 2-propanamine; Benzenesulfonic acid, dodecyl-, branched, compounds with 2-propanamine	≥3 - ≤7	90218-35-2
2,2' -oxybisethanol	diethylene glycol; 2,2'-oxydiethanol; Ethanol, 2,2'-oxybis-; 2,2'-Oxybis[ethanol]; 2,2'-Oxybis[ethanol]; diethylene glycol propylene glycol triethanolamine titanate complexes (CAS RN 68784- 48-5) dissolved in diethylene glycol (CAS RN 111-46-6); digol; DEG; 3-Oxypentane-1,5-diol; Diglycol	≥3 - ≤7	111-46-6
Alcohols, C11-14-iso-, C13-rich, ethoxylated	alcohols, C11-14-isoalcohols, C13-rich, ethoxylated; Ethoxylated branched C11-14, C13 rich alcohols; alcohols, C11-14-isoalcs., C13-rich, ethoxylated; Alcohols, C11-14-iso-, C13-rich, ethoxylated; Alcohols, C11-14-iso-, C13 rich, ethoxylated; Ethoxylated branched c11-c14, c13-rich alcohols; Ethoxylated branched C11-14, C13-rich alcohols; Ethoxylated isoalcohols(C11-14, C13 rich); Polyoxyalkylene (C2-4,8) monoalkyl (or alkenyl) (C1-24) ether (n1-150); Alcohols, (C=11-14)-iso-, (C=13)-rich, ethoxylated; POLYETHOXYLATED TRIDECYL ALCOHOL; Tridecyl alcohol ethoxylate	≥1 - ≤5	78330-21-9
potassium hydroxide	caustic potash; Potassium hydrate; Lye; potassium hydroxide, solid; potassium hydroxide, in aqueous solution; caustic potash, solid; E 525; potassium lye; caustic potash, in aqueous solution; Potassa; POTASSIUM HYDROXIDE (K (OH))	≥0.5 - ≤1.5	1310-58-3

SUB codes represent substances without registered CAS Numbers.

Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Harmful if swallowed.

Section 4. First aid measures

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon oxides
nitrogen oxides
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Special precautions** : Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Vapors are heavier than air and may spread along floors. If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Talc , not containing asbestiform fibres	ACGIH TLV (United States, 1/2025) TWA 8 hours: 2 mg/m ³ . Form: Respirable fraction.
ethanediol	OSHA PEL Z3 (United States) TWA: 2 mg/m ³ .
carbon black	ACGIH TLV (United States, 1/2025) STEL 15 minutes: 10 mg/m ³ . Form: Inhalable fraction. Aerosol only.. STEL 15 minutes: 50 ppm. Form: Vapor fraction. TWA 8 hours: 25 ppm. Form: Vapor fraction.
Benzenesulfonic acid, dodecyl-, branched, compd. with 2-propanamine	ACGIH TLV (United States, 1/2025) TWA 8 hours: 3 mg/m ³ . Form: Inhalable fraction.
2,2' -oxybisethanol	OSHA PEL (United States, 5/2018) TWA 8 hours: 3.5 mg/m ³ .
Alcohols, C11-14-iso-, C13-rich, ethoxylated	None.
potassium hydroxide	None.
	None.
	ACGIH TLV (United States, 1/2025) C: 2 mg/m ³ .

Biological exposure indices

No exposure indices known.

Consult local authorities for acceptable exposure limits.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Section 8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.
Color : Not available.
Odor : Characteristic.
Odor threshold : Not available.
pH : Not applicable.
Melting point/freezing point : Not available.

Product code 00355821**Date of issue** 30 June 2026**Version** 1.04**Product name** 96-2 PPG CUSTOM COLORANT CONCENTRATE B-LAMP BLACK

Section 9. Physical and chemical properties

Boiling point or initial boiling point and boiling range : >37.78°C (>100°F)

Flash point : Closed cup: 113.33°C (236°F) [Product does not sustain combustion.]

Evaporation rate : Not available.

Flammability : Not available.

Lower and upper explosion limit/flammability limit : Not available.

Vapor pressure :

Ingredient name	Vapor Pressure at 20°C			Vapor pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
water	17.5	2.3				

Relative vapor density : Not available.

Relative density : 1.35

Density (lbs / gal) : 11.27

% Solid. (w/w) : 54.67

Solubility(ies) :

Media	Result
cold water	Not soluble

Miscible with water : No.

Partition coefficient: n-octanol/water : Not applicable.

Auto-ignition temperature :

Ingredient name	°C	°F	Method
2,2' -oxybisethanol	229	444.2	DIN EN 14522-S

Decomposition temperature : Not available.

Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Section 10. Stability and reactivity

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:
carbon oxides nitrogen oxides metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Result

ethanediol

Rat - Oral - LD50

4700 mg/kg

Rabbit - Dermal - LD50

9.53 g/kg

carbon black

Rat - Oral - LD50

>10 g/kg

OECD 401

2,2' -oxybisethanol

Rabbit - Dermal - LD50

11890 mg/kg

Toxic effects: Behavioral - Coma Lung, Thorax, or Respiration -
Dyspnea Changes in Chemistry or Temperature - Body
temperature decrease

Rat - Oral - LD50

12000 mg/kg

Toxic effects: Brain and Coverings - Other degenerative changes
Liver - Other changes Kidney, Ureter, and Bladder - Other
changes

potassium hydroxide

Rat - Oral - LD50

273 mg/kg

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Section 11. Toxicological information

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Talc , not containing asbestiform fibres	-	2A	-
carbon black	-	2B	-

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name

Talc , not containing asbestiform fibres

Benzenesulfonic acid, dodecyl-, branched,
compd. with 2-propanamine

Result

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
(Respiratory tract irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
(Respiratory tract irritation) - Category 3

Section 11. Toxicological information

Specific target organ toxicity (repeated exposure)

Product/ingredient name

ethanediol

2,2' -oxybisethanol

Result

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) (oral) - Category 2

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) (oral) - Category 2

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. Defatting to the skin.
- Ingestion** : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
dryness
cracking
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

- Conclusion/Summary** : There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Section 11. Toxicological information

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity : May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
96-2 PPG CUSTOM COLORANT CONCENTRATE B-LAMP BLACK	1411.2	N/A	N/A	N/A	N/A
ethanediol	500	9530	N/A	N/A	N/A
Benzenesulfonic acid, dodecyl-, branched, compd. with 2-propanamine	500	N/A	N/A	N/A	N/A
2,2' -oxybisethanol	500	11890	N/A	N/A	N/A
Alcohols, C11-14-iso-, C13-rich, ethoxylated	500	N/A	N/A	N/A	N/A
potassium hydroxide	500	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Not available.

Section 12. Ecological information

Conclusion/Summary [Product] : Not available.

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
ethanediol	-1.36	-	Low
2,2' -oxybisethanol	-1.98	-	Low

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	DOT	TDG	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	-	-	-
Class(es)	9	-	-	-
Packing group	III	-	-	-
Environmental hazards	No.	No.	No.	No.

Product code 00355821

Date of issue 30 June 2026

Version 1.04

Product name 96-2 PPG CUSTOM COLORANT CONCENTRATE B-LAMP BLACK

14. Transport information

Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.	Not applicable.
-----------------------------	-----------------	-----------------	-----------------	-----------------

Additional information

DOT : The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

Product RQ (lbs) : 24103.4

RQ substances : (ethanediol)

TDG : None identified.

IMDG : None identified.

IATA : None identified.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

U.S. Federal regulations

TSCA 5(a)2 - Proposed significant new use rules:

5-chloro-2-methyl-2H-isothiazol-3-one

Listed

P-96-1251

3(2H)-Isothiazolone, 2-methyl-

Listed

P-96-1250

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : ACUTE TOXICITY (oral) - Category 4
SKIN IRRITATION - Category 2
SERIOUS EYE DAMAGE - Category 1
CARCINOGENICITY - Category 1B
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
HNOC - Defatting irritant

Composition/information on ingredients

Section 15. Regulatory information

Name	%	Classification
Talc , not containing asbestiform fibres	≥15 - ≤40	CARCINOGENICITY - Category 1B SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
ethanediol	≥10 - ≤30	ACUTE TOXICITY (oral) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
carbon black	≥5 - ≤10	HNOC - Defatting irritant COMBUSTIBLE DUSTS
Benzenesulfonic acid, dodecyl-, branched, compd. with 2-propanamine	≥3 - ≤7	CARCINOGENICITY - Category 2 COMBUSTIBLE DUSTS ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
2,2' -oxybisethanol	≥3 - ≤7	ACUTE TOXICITY (oral) - Category 4 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
Alcohols, C11-14-iso-, C13-rich, ethoxylated potassium hydroxide	≥1 - ≤5 ≥0.5 - ≤1.5	ACUTE TOXICITY (oral) - Category 4 SERIOUS EYE DAMAGE - Category 1 ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION - Category 1A SERIOUS EYE DAMAGE - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	ethanediol	107-21-1	≥10 - ≤30
Supplier notification	ethanediol	107-21-1	≥10 - ≤30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

⚠ WARNING: This product can expose you to Carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Ingredient name	No significant risk level	Maximum acceptable dosage level
Carbon black	-	-

Inventory list

Australia	: At least one component is not listed.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Eurasian Economic Union	: Russian Federation inventory: Not determined.
Japan	: Japan inventory (CSCL): At least one component is not listed. Japan inventory (ISHL): Not determined.

Section 15. Regulatory information

New Zealand	: At least one component is not listed.
Philippines	: All components are listed or exempted.
Republic of Korea	: All components are listed or exempted.
Taiwan	: All components are listed or exempted.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: All components are active or exempted.
Viet Nam	: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (oral) - Category 4	Calculation method
SKIN IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
CARCINOGENICITY - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method

History

Date of printing	: 6/30/2026
Date of issue/Date of revision	: 6/30/2026
Date of previous issue	: 5/1/2026

Section 16. Other information

Version : 1.04
EHS

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
DOT = Department of Transportation
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
IMO = International Maritime Organization
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973
as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
TDG = Transportation of Dangerous Goods
UN = United Nations

References : Not available.

▣ Indicates information that has changed from previously issued version.

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein or from failure to observe the recommended measures for storage and handling of the products. Final determination of suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. All materials may present unknown hazards and should be used with caution.