

SAFETY DATA SHEET



Date of issue/Date of revision 22 October 2026

Version 1.14

Section 1. Identification

Product name : 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT & PRIMER EGGSHELL ULTRA DEEP BASE

Product code : 00434914

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications, Used by spraying.

Use of the substance/ mixture : Coating.

Uses advised against : Not applicable.

Manufacturer : The Pittsburgh Paints Co.
500 Cranberry Woods Drive,
Cranberry Township, PA 16066

Emergency telephone number : 1-833-477-1553 (U.S. and Canada)
SETIQ Interior de la República: 800-00-214-00 (México)

Technical Phone Number : 1-800-441-9695 (U.S. and México)
1-800-387-2253 (Canada)

Section 2. Hazards identification

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 24.8% (oral), 27.4% (dermal), 24.8% (inhalation)

GHS label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Product code 00434914**Date of issue** 22 October 2026 **Version** 1.14**Product name** 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT & PRIMER EGGSHELL ULTRA DEEP BASE

Section 2. Hazards identification

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains isothiazolinones. May cause allergic reaction. Emits toxic fumes when heated.

Hazards not otherwise classified : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Other means of identification : Not available.

Ingredient name	Synonyms	%	CAS number
Kaolin	Argilla; Porcelain clay; Hydrite; Hydrated aluminum silicate; Clay; China clay; μ -[1,3-dioxodisiloxane-1,3-diolato(2-)- κ O1: κ O3](dioxo)dialuminum dihydrate; E 559; kaolin; China clay; aluminium silicate, hydrated; oxo-oxoalumanyloxy-[oxo(oxoalumanyloxy)silyl]oxysilane dihydrate; Clay (kaolin); KAOLIN DUST	$\geq 1 - \leq 5$	1332-58-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Product code 00434914

Date of issue 22 October 2026 **Version** 1.14

Product name 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT
& PRIMER EGGSHELL ULTRA DEEP BASE

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Special precautions** : If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Kaolin	ACGIH TLV (United States, 1/2025) TWA 8 hours: 2 mg/m ³ . Form: Respirable fraction. OSHA PEL (United States, 5/2018) TWA 8 hours: 15 mg/m ³ . Form: Total dust. TWA 8 hours: 5 mg/m ³ . Form: Respirable fraction.

Biological exposure indices

No exposure indices known.

Consult local authorities for acceptable exposure limits.

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product code 00434914

Date of issue 22 October 2026 **Version** 1.14

Product name 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT & PRIMER EGGSHELL ULTRA DEEP BASE

Section 8. Exposure controls/personal protection

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. The respiratory protection shall be in accordance to 29 CFR 1910.134.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Liquid.
Color : Various
Odor : Alcohol-like.
Odor threshold : Not available.
pH : 9
Melting point/freezing point : Not available.
Boiling point or initial boiling point and boiling range : 100°C (212°F)
Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]
Evaporation rate : 0.05 (butyl acetate = 1)
Flammability : Not available.
Lower and upper explosion limit/flammability limit : Not available.
Vapor pressure : 3.3 kPa (25 mm Hg)
Relative vapor density : Not available.
Relative density : 1.11
Density (lbs / gal) : 9.26
% Solid. (w/w) : 39.243
Solubility(ies) :

Media	Result
cold water	Soluble

Miscible with water : Yes.
Partition coefficient: n-octanol/water : Not applicable.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C (104°F)): >21 mm²/s (>21 cSt)

Particle characteristics

Median particle size : Not applicable.

Product code 00434914

Date of issue 22 October 2026 **Version** 1.14

Product name 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT
& PRIMER EGGSHELL ULTRA DEEP BASE

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Depending on conditions, decomposition products may include the following materials:
metal oxide/oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name

Kaolin

Result

Rat - Oral - LD50

>5000 mg/kg

Rat - Inhalation - LC50 Dusts and mists

>5.07 mg/l [4 hours]

Conclusion/Summary [Product] : Not available.

Skin corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Serious eye damage/eye irritation

Not available.

Conclusion/Summary [Product] : Not available.

Respiratory corrosion/irritation

Not available.

Conclusion/Summary [Product] : Not available.

Section 11. Toxicological information

Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary [Product] : Not available.

Respiratory

Conclusion/Summary [Product] : Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary [Product] : Not available.

Carcinogenicity

Not available.

Conclusion/Summary [Product] : Not available.

Reproductive toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : No known significant effects or critical hazards.

Section 11. Toxicological information

Skin contact : No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary [Product] : Not available.

General : No known significant effects or critical hazards.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

N/A

Product code 00434914

Date of issue 22 October 2026 **Version** 1.14

Product name 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT & PRIMER EGGSHELL ULTRA DEEP BASE

Section 12. Ecological information

Toxicity

Not available.

Conclusion/Summary [Product] : Not available.

Persistence and degradability

Not available.

Conclusion/Summary [Product] : Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/Water partition coefficient : Not available.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

	DOT	TDG	IMDG	IATA
UN number	Not regulated.	UN3082	UN3082	UN3082
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PAINT)
Class(es)	-	9	9	9

14. Transport information

Packing group	-	III	III	III
Environmental hazards	No.	Yes.	Yes.	Yes.
Marine pollutant substances	Not applicable.	(octhiline (ISO))	(octhiline (ISO))	Not applicable.

Additional information

- DOT** : None identified.
- TDG** : Non-bulk packages of this product are not regulated as dangerous goods when transported by road or rail.
- IMDG** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.
- IATA** : This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to IMO instruments : Not applicable.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are active or exempted.

U.S. Federal regulations

TSCA 5(a)2 - Proposed significant new use rules:

3(2H)-Isothiazolone, 2-methyl-	Listed	P-96-1250
5-chloro-2-methyl-2H-isothiazol-3-one	Listed	P-96-1251

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

SARA 313

Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	hexachlorobenzene	118-74-1	≤0.1
Supplier notification	hexachlorobenzene	118-74-1	≤0.1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Inventory list

- | | |
|--------------------------------|--|
| Australia | : At least one component is not listed. |
| Canada | : All components are listed or exempted. |
| China | : At least one component is not listed. |
| Eurasian Economic Union | : Russian Federation inventory: Not determined. |
| Japan | : Japan inventory (CSCL): At least one component is not listed.
Japan inventory (ISHL): Not determined. |
| New Zealand | : At least one component is not listed. |
| Philippines | : At least one component is not listed. |
| Republic of Korea | : At least one component is not listed. |
| Taiwan | : Not determined. |
| Thailand | : Not determined. |
| Turkey | : Not determined. |
| United States | : All components are active or exempted. |
| Viet Nam | : Not determined. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)

Product code 00434914

Date of issue 22 October 2026 **Version** 1.14

Product name 589-40 PITTSBURGH PAINTS ACRI-SHIELD MAX EXTERIOR 100% ACRYLIC PAINT
& PRIMER EGGSHELL ULTRA DEEP BASE

Section 16. Other information



Procedure used to derive the classification

Not classified.

History

Date of printing : 10/22/2026
Date of issue/Date of revision : 10/22/2026
Date of previous issue : 9/24/2026
Version : 1.14
EHS

Key to abbreviations

: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
DOT = Department of Transportation
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
IMO = International Maritime Organization
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
TDG = Transportation of Dangerous Goods
UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein or from failure to observe the recommended measures for storage and handling of the products. Final determination of suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. All materials may present unknown hazards and should be used with caution.