

Architectural Coatings

Speedhide MaxBuild Interior High Build Drywall Surfacers**GENERAL DESCRIPTION**

Speedhide MaxBuild High Build Drywall Surfacers is a quick drying, interior, vinyl acrylic latex drywall surfacer for use as a first coat on unprimed/unpainted drywall. Recommended for high build spray application over new drywall. The surfacer can be used to replace the typical two-step process of applying a skim coat of joint compound to the finished drywall, followed by a coat of primer. This product ensures that the finish coat will have a smooth and uniform sheen. *Speedhide MaxBuild* High Build Drywall Surfacers, when applied according to recommended spread rates, will achieve a GA-214 ASTM C840 Level 5 gypsum board finish.

RECOMMENDED SUBSTRATES

Gypsum Wallboard-Drywall

CONFORMANCE STANDARDS

Compliant with all US VOC regulations as of 08/2026

PRODUCT INFORMATION

6-1 White Primer

Do not tint.

PACKAGING

5-Gallon (18.9 L)

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. Must be topcoated. Apply when air, product and surface temperatures are between 50°F (10°C) and 90°F (32°C).

PROTECT FROM FREEZING.

FEATURES / BENEFITS**Features**

Less than 50 g/L VOC
Low Odor
High Build
Fast Drying
Easy to Sand

PRODUCT DATA

PRODUCT TYPE: Vinyl Acrylic Latex
SHEEN: Flat, 0-3 @60° & 85°
VOLUME SOLIDS: 46% +/- 2%
WEIGHT SOLIDS: 66% +/- 2%
WEIGHT/GALLON: 13.3 lbs. (6.0 kg) +/- 0.2 lbs. (91 g)
VOC: < 50 g/L (0.4 lbs./gal.)

COVERAGE: Approximately 80 to 107 sq. ft. (7 to 10 sq. meters) per U.S. Gallon (3.78L) on smooth, nonporous surfaces.

Wet Film Thickness: 15 to 20 mils
Wet Microns: 381 to 508
Dry Film Thickness: 6.9 to 9.2 mils
Dry Microns: 175 to 234

Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing. Some colors, drastic color changes, or porous substrates may require more than one coat to achieve a uniform finish.

DRYING TIME: Dry time @ 77°F (25°C); 50% relative humidity.

To Touch: 1 hour
To Recoat: 4 hours
To Full Cure: 30 days

Drying times listed may vary depending on temperature, humidity, film build, color, and air movement. Wait at least 30 days after painting before cleaning the surface with a non-abrasive, mild cleanser. Very deep colors may require longer to fully cure.

CLEANUP: Clean tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

Benefits

Meets the most stringent VOC regulations nationwide
Ideal for use in occupied spaces
Achieves a GA-214 ASTM C840 Level 5 gypsum board finish
Saves Time
Saves Labor

GENERAL SURFACE PREPARATION

Paint only clean, dry, chalk, and dust-free drywall. A minimum Level 4 drywall finish as defined by the Gypsum Association Publication GA-214 and ASTM C840 is recommended before application of this surfacer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

GYPSUM WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust prior to priming the substrate.

APPLICATION INFORMATION

Stir thoroughly before using and occasionally when in use. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

Application Equipment: For best appearance, an airless sprayer should be used. The product may be applied by roller, but two coats may be required to obtain recommended film thickness.

Airless Spray: Use a pump with a 28:1 pump ratio, .023" to .031" tip, and a 1/4" high-pressure material hose. Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Roller (nap roller cover): 1/2" - 3/4"

Thinning: Do not thin.

Permissible temperatures during application:

Material: 50 to 90°F (10 to 32°C)

Ambient: 50 to 90°F (10 to 32°C)

Substrate: 50 to 90°F (10 to 32°C)

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2026 The Pittsburgh Paints Co. All Rights Reserved. *Speedhide* is a registered trademark, and *MaxBuild*, and the *P Logo & Pittsburgh Paints* are trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.