

*Olympic Elite* Solid Color Stain + Sealant

GENERAL DESCRIPTION

Olympic Elite is a premium stain + sealant formulated with pigments that deliver rich, color clarity while providing a durable *ALL-CLIMATE PROTECTION PACKAGE™*. *Olympic Elite* is recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture, and other wood surfaces.

RECOMMENDED SUBSTRATES

Wood	Siding
Decks	Railings
Fences	Outdoor Furniture

FEATURES / BENEFITS

A Lifetime of Durability & Beauty
4 Season Protection
Waterproofing Protection
Resists Peeling & Cracking
Provides Mildew Resistant Finish

PRODUCT INFORMATION

80301	White/Tintable Base 1
80302	Tintable Base 2*

*Must be tinted. Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

PACKAGING

1-Gallon (3.78 L)
5-Gallon (18.9 L)

Not all products available in all sizes.

PRODUCT DATA

PRODUCT TYPE:	Acrylic
VOLUME SOLIDS*:	34% +/- 2%
WEIGHT SOLIDS*:	44% +/- 2%
WEIGHT/GALLON*:	9.8 lbs. (4.5 kg) +/- 0.2 lbs. (91 g)
VOC:	< 100 g/L (0.8 lbs./gal.)

*Product data calculated on 80301.

COVERAGE: Approximately 350 to 500 sq. ft. (32 to 47 sq. meters) per gallon (3.78 L) depending on application, wood texture, and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

DRYING TIME: Normally dries to the touch in 30 minutes when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Allow 2 to 4 hours between coats or before recoating. Application in high humidity or in temperatures below 50°F (10°C) may prolong drying times. Allow 24 to 48 hours of drying time before light foot traffic and 72 hours before normal foot traffic or replacing furniture. Allow new stain to cure 30 days before washing.

READY FOR RAIN: Allow paint film to dry for at least 2 hours prior to expected rain when temperatures are at or above 60°F (16°C) and 50 to 70% relative humidity. Lower temperatures, higher humidity, or deeper colors may increase drying time and rain readiness time.

CLEANUP: Clean brushes and tools with warm, soapy water.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: Over 200°F (93°C)

LIMITATIONS OF USE

FOR EXTERIOR USE ONLY.

Apply when air and surface temperatures are between 35°F (2°C) and 90°F (32°C) and at least 5°F (3°C) above the dew point. Air and surface temperatures must remain between 35°F (2°C) and 90°F (32°C) for the next 24 hours. Avoid staining in direct sunlight or on hot surfaces.

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

PROTECT FROM FREEZING.

Olympic Elite Solid Color Stain + Sealant

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Remove loose, peeling stain by sanding, scraping, or wire brushing. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying stain. After rinsing, allow wood to dry. Remove grade stamps or pencil marks by sanding.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. In Canada, contact a regional Health Canada office. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

PRIME: THIS PRODUCT IS SELF-PRIMING OVER MOST SUBSTRATES. Some woods, such as cedar and redwood, contain high amounts of tannin, a colored wood extract. The first coat of stain may show some discoloration, but the tannins will be trapped in the first coat of stain. A second coat will result in a uniform appearance.

APPLICATION INFORMATION

Stir thoroughly and often during use. When using more than one container of the same color, intermix to ensure color uniformity. Apply to a small area and allow stain to dry to ensure acceptable appearance and penetration. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.** Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our website or by calling 1-800-441-9695.

Application Method: Apply two thin coats. Some colors, or drastic color changes, may require a third coat to achieve a uniform finish. To help avoid lap marks, apply to only a few boards at a time, and maintain a wet edge. Do not saturate or puddle on horizontal surfaces.

Application Equipment: Apply with a high-quality brush, paint/stain-pad, or with spray equipment. When applying by roller or spray, always back-brush for best results.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do not thin.

Permissible temperatures during application:

Material: 35 to 90°F (2 to 32°C)

Ambient: 35 to 90°F (2 to 32°C)

Substrate: 35 to 90° (2 to 32°C)

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2026 The Pittsburgh Paints Co. All Rights Reserved. *Olympic*, *Olympic and Design*, and *Paintbrush Design* are registered trademarks, and *All-Climate Protection Package*, *Elite*, and the *P Logo* & *Pittsburgh Paints* are trademarks of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



The Pittsburgh Paints Company
500 Cranberry Woods Drive
Cranberry Township, PA 16066
www.olympic.com

Technical Services
1-800-441-9695

80301 - 8/2026