PPG PAINTS™ WALLPRO® 34-1XIC

PPG Architectural Coatings — Interior Latex Ceiling Paint, Flat

GENERAL DESCRIPTION

WallPro Interior Latex Ceiling Paint is ideal for use on properly prepared interior ceilings composed of primed or previously painted drywall, plaster, masonry, and wood.

RECOMMENDED SUBSTRATES

Concrete	Concrete/Masonry Block
Ferrous Metal	Gypsum Wallboard
Plaster	Wood

See details in the "recommended primers" section.

CONFORMANCE STANDARDS

- Low volatile organic compound (VOC) content less than the requirements of the Canadian VOC Concentration Limiting Regulation for Architectural Coatings.
- Can help earn LEED® 2009 credits

TINTING AND BASE INFORMATION

34-1XIC White **DO NOT TINT.**

Some colours, drastic colour changes, or porous substrates may require more than one coat to achieve a uniform finish.

PACKAGING

3.78 L

PRODUCT DATA

PRODUCT TYPE: Vinyl-Acrylic Latex
SHEEN: Flat 0 to 8 % (85° Gloss Meter)
VOLUME SOLIDS*: 13% ± 2%
WEIGHT SOLIDS*: 25% ± 2%
VOC*: < 50 g/L
DENSITY*: 1.2 kg/L
*Product data calculated on product 34-1XIC.

SPREADING RATE PER COAT: Approximately 37 square metres (400 sq. ft.) per 3.78 litres on primed, smooth, nonporous surfaces.

Wet Film Thickness: 102 microns, 4.0 mils
Dry Film Thickness: 13 microns, 0.5 mils

Coverage figures do not include loss due to surface irregularities and porosity or material losses due to application method or mixing.

DRYING: Dry time @ 25°C (77°F); 50% relative humidity.

To Touch:	1 hour
To Recoat:	4 hours minimum
Before cleaning:	30 days
Full curing:	30 days

Drying times listed may vary depending on temperature, humidity, film build, colour, and air movement.

Permissible temperatures during the application:

Material:	10 to 32°C	50 to 90°F
Ambient:	10 to 32°C	50 to 90°F
Substrate:	10 to 32°C	50 to 90°F

CLEANUP: Remove as much product quantity as possible and clean tools with lukewarm soapy water immediately after use.

WASHING INSTRUCTIONS: Wait at least 30 days before cleaning the surface (longer in conditions of high humidity or low temperature) use a non-abrasive mild cleaner.

DISPOSAL: Consult your municipality in order to dispose of paint residues according to environmental regulations. Do not pour down a drain or storm sewer.

FLASH POINT: Over 93 °C (200 °F)

FEATURES / BENEFITS

Features	Benefits
Less than 50 g/L VOC	Content less than the requirements of the Canadian VOC Concentration Limiting Regulation for Architectural Coatings.
Good hiding power and coverage	Saves time and lowers material costs
Low Spatter	Minimizes soiling
Easy to apply	Saves time and labour
Waterborne formula	Easy soap and water clean-up; saves time
Can help earn *LEED* 2009 credits	Contributes to sustainable design

LIMITATIONS OF USE

FOR INTERIOR USE ONLY. USE WITH ADEQUATE VENTILATION. **KEEP OUT OF REACH OF CHILDREN.**
PROTECT FROM FREEZING.

Apply when air, surface and product temperatures are between 10°C to 32°C (50°F to 90°F).

Not formulated to be used in kitchens or bathrooms.

Do not use on floors, in high humidity areas.

GENERAL SURFACE PREPARATION

Surfaces to be coated must be dry, clean, sound, and free from all contamination including loose and peeling paint, dirt, grease, oil, wax, concrete curing agents and bond breakers, chalk, efflorescence, mildew, rust, product fines, and dust.

Sand all glossy, rough, and patched surfaces.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wear suitable respiratory protective equipment. **WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Contact a regional Health Canada office for more information.

Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation. Prime all bare surfaces with the appropriate primer.

Previously Painted Alkyd Surfaces in Good Condition: Prime surface with an appropriate primer.

CONCRETE: New concrete should cure for at least 30 days and preferably 90 days prior to priming and topcoating. The pH of the substrate must be less than 10 before priming with an alkali resistant primer. Remove loose paint, chalk, and efflorescence by wire brushing, scraping, sanding, and/or pressure washing.

FERROUS METAL: The surface must be cleaned thoroughly to remove any dust, rust, oil, and surface contaminants, and then primed.

GYPSUM WALLBOARD: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting the substrate.

PLASTER: Plaster or other alkaline surfaces should be allowed to cure for at least 30 days prior to prime with an alkali resistant primer.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, and then primed. Any knots or resinous areas must be primed before painting. Countersink all nails, putty flush with surface, then prime.

SOLUBLE STAINS: Apply a SEAL GRIP® primer over the stained area prior to coating, to avoid bleeding the stain into the topcoat.

Before use, be sure to read and follow the instructions and warnings on the label.

Contact your local representative for any additional surface preparation guidelines.

RECOMMENDED PRIMERS

Concrete	4-603C, 17-921XIC	**Ferrous Metal**	6-208C, 6-212C
Gypsum Wallboard	6-2C, 6-4C, 9-900C, 12-900XIC, 34-2C	**Plaster**	17-921XIC
Wood	6-2C, 9-900C, 12-900XIC, 17-921XIC, 34-2C		

APPLICATION INFORMATION

KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available from your retailer, through our website or by calling 1-800-463-7426.

Stir thoroughly before use and occasionally during use. When using more than one container of the same colour, intermix to ensure colour uniformity.

Application Equipment: Apply with a high quality synthetic brush, roller, paint pad, or by spray equipment. Where necessary, apply a second coat and allow each coat to dry thoroughly before applying the next coat.

Brush: High quality polyester/nylon brush.

Roller: 10 to 20 mm (3/8 – 3/4 in.) nap synthetic roller cover.

Airless Spray: Pressure 2000 psi, tip 0.015 in. - 0.021 in.

Spray equipment must be handled with due care and in accordance with the manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do not thin.

Permissible temperatures during application:

Material: 10°C to 32°C **Ambient:** 10°C to 32°C **Substrate:** 10°C to 32°C

PRECAUTIONS

Keep out of the reach of children. Keep containers tightly closed and sealed until ready for use.
Before using the products listed in this publication, carefully read each product label and follow directions for its use. Use personal protective equipment as required. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation.

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection.

FIRST AID: If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. In case of contact, immediately flush skin with plenty of water while removing contaminated clothing and shoes. Get medical attention if irritation develops. If inhaled, remove to fresh air. If experiencing respiratory symptoms call poison centre or doctor/physician.

For workplace use, an SDS are available from your retailer, through our website or by calling 1 800 463-7426.
EMERGENCY SPILL INFORMATION: 1 514 645-1320 or 1 800 463-7426.

LIMITED WARRANTY

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special or consequential damages.

The *PPG Paints* is a registered trademark of PPG Industries Ohio, Inc. *WallPro* is a registered trademark of PPG Architectural Finishes, Inc. *LEED* is a registered trademark of the US Green Building Council.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1-866-660-2220.

PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpaints.com

PPG Architectural Coatings Canada Inc.
2505, de la Metropole
Longueuil, QC, Canada, J4G 1E5

Technical Services 450 442-2220
1 866 660-2220
Fax: 450 679-8893
1 800 278-8893

Architect/Specifier
1-888-PPG-IDEA