

GENERAL DESCRIPTION

This premium ceiling paint goes on as a light pink colour and dries to a bright white so you can see where you are painting and prevent "missed" spots on the ceiling.

No Miss Flat Finish Interior Latex Ceiling Paint provides a beautiful, premium finish to interior ceilings.

Ideal for use on properly prepared, interior ceilings composed of primed or previously painted drywall, plaster, masonry, and wood.

RECOMMENDED SUBSTRATES

Concrete	Gypsum Wallboard-Drywall
Masonry	Plaster
Primed Metal	Wood

See details in the recommended primers section.

CONFORMANCE STANDARDS

- Complies with the Canadian Volatile Organic Compound Concentration Limits for Architectural Coatings Regulations.
- Can earn LEED v4 credit

TINTING AND BASE INFORMATION

17-46XIC White

Do not tint.

PACKAGING

3.78 L

PRODUCT DATA

PRODUCT TYPE:	Vinyl-Acrylic Latex Paint
SHEEN:	Flat: 5 to 10 % (85° Gloss Meter)
VOLUME SOLIDS*:	25% ± 2%
WEIGHT SOLIDS*:	44% ± 2%
VOC*:	< 50 g/L
DENSITY*:	1.3 kg/L

*Product data calculated on product 17-46XIC.

SPREADING RATE PER COAT From 19 to 28 square metres (200 to 300 sq. ft.) per 3.78 litres on primed, smooth, nonporous surfaces.

Wet Film Thickness: 5.3 to 8.0 mils (136 to 204 microns)

Dry Film Thickness: 1.3 to 2.0 mils (34 to 51 microns)

Coverage figures do not include material loss due to application. Some colours, drastic colour changes, or porous surfaces may require additional coats of paint to achieve a uniform finish.

DRYING TIME: Dry time @ 25°C (77°F); 50% relative humidity.

To Touch: 1 hour

To Recoat: 2 to 4 hours minimum

Full Cure: 30 days

Pink color will fade upon drying

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

Permissible temperatures during the application:

Material:	10 to 32°C	50 to 90°F
Ambient:	10 to 32°C	50 to 90°F
Substrate:	10 to 32°C	50 to 90°F

CLEANUP: Clean tools with warm, soapy water.

WASHING INSTRUCTIONS: Wait at least 30 days before cleaning the surface and use a non-abrasive, mild cleaner.

DISPOSAL: Consult your municipality about proper disposal procedure of residue in accordance with the laws and respect the environment. Do not pour down a drain or storm sewer.

FLASH POINT: Over 93°C (200°F)

FEATURES / BENEFITS

Features

Goes on pink and dries to white in about 30 min. - 1 hour
Low Spatter
Quickly Dries to a True, Flat Finish

Latex formula
Low VOC formula
Excellent hiding power

Benefits

Easy Tracking Ensures No Miss Results.
Easy to work with, less mess.
Prevents glare, hides minor surface imperfections, dries evenly and is less likely to show roller lap marks.
Easy soap and water clean up.
Is low odour and minimizes negative impact on air quality.
Hides surface imperfections and provides better-looking results.

LIMITATIONS OF USE

FOR INTERIOR USE ONLY.

PROTECT FROM FREEZING.

Apply only when air, surface, and product temperatures are between 10°C (50°F) and 32°C (90°F).

Not recommended for use on steps or floors.

Not intended for use on walls.

Do not use in bathrooms or high-humidity areas.

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose, peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks or open seams. Sand all glossy, rough, and patched surfaces.

Remove loose paint, chalk, and efflorescence by wire brushing, scraping and/or sanding.

Mildew: Remove mildew with a solution of household bleach (1 part household bleach to 3 parts of water). Before use, be sure to read and follow the instructions and warnings on the label.

Sand all glossy, rough or patched surfaces. Feather back all rough edges to sound surface by sanding.

Prime all bare and porous substrates with an appropriate primer.

PRECAUTION: Dry sanding will give rise to dust and/or hazardous fumes. Wear suitable respiratory protective equipment. WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact a regional Health Canada office for more information.

Primers: Prime all bare surfaces with the appropriate primer.

Concrete, Stucco, or Masonry:

- Plaster, concrete, and masonry must be completely dry, free of efflorescence, and allowed to cure for 30 days prior to priming and painting. Remove surface dust and prime entire surface prior to painting.
- Prior to priming or top coating, substrate should cure for at least 30 days and preferably 90 days, the moisture content must be less than 12% and the pH must be less than 10. If pH is greater than 10, prime with an alkali resistant primer.
- Surfaces previously coated with water thinned cement-based paint must be prepared with extra care. Check adhesion by applying a piece of masking tape. If the material appears to be adhering tightly, a masonry sealer may be applied to seal the surface. If the sealer peels off and has loose particles, remove all chalking or crumbling material, re-seal and re-check adhesion.
- Fill block with appropriate block filler.

Previously Painted Alkyd Surfaces in Good Condition: Prime surface with an appropriate primer.

FERROUS METAL: Prior to priming and top coating, the surface must be cleaned thoroughly to remove any dust, rust, oil and surface contaminants.

GYPSON WALLBOARD-DRYWALL: Nails or screws should be countersunk, and they along with any indentations should be mudded flush with the surface, sanded smooth and cleaned to remove any dust, then prime prior to painting.

PLASTER: Plaster or other alkaline surfaces should be allowed to cure for at least 30 days prior to painting.

WOOD: Unpainted wood or wood in poor condition should be sanded smooth, wiped clean, and then primed. Any knots or resinous areas must be primed before painting. Countersink all nails or screws, putty flush with the surface, then prime prior to painting.

Contact your local representative for any additional surface preparation guidelines.

RECOMMENDED PRIMERS

Concrete, Masonry	6-7C (block fillers), 4-603C, 17-921C (primers, sealers)
Ferrous Metal	6-208C, 6-212C
Gypsum Wallboard-Drywall	6-2C, 6-4C, 9-900C, 12-900C
Plaster	4-603C, 17-921C
Wood	6-2C, 9-900C, 12-900C, 17-921C

APPLICATION INFORMATION

Stir thoroughly. Do not thin.

Application Equipment: Apply with a high-quality brush, roller (nap size – 13 mm), paint pad, or by airless spray equipment. When using more than one container of the same colour, intermix to ensure colour uniformity.

Brush: High quality polyester/nylon brush.

Roller: 13 mm (3/8 – 3/4 in.) nap synthetic roller cover.

Airless Spray: Pressure 2000 psi, tip 0.015 in. - 0.021 in.

Spray equipment must be handled with due care and in accordance with the manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Thinning is not usually required. If necessary, add no more than 118 mL of water per 3.78L of paint.

PRECAUTIONS

MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. Avoid breathing vapours, spray, or mists. Avoid contact with skin and eyes. Wear protective gloves/clothing and eye/face protection. Keep out of reach of children. **FIRST AID TREATMENT:** If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water. If breathed in, move person to fresh air. Contains: talc, not containing asbestiform fibres; titanium dioxide. Contains isothiazolinones. May cause allergic reaction. Keep container tightly closed and sealed until ready for use. For workplace use, an SDS is available from your retailer or by calling 1-800-463-7426. EMERGENCY SPILL INFORMATION: 514-645-1320.

LIMITED WARRANTY

PPG Architectural Coatings Canada, Inc. warrants performance of its products to its intended use if properly applied in accordance with the label directions and the specifications of the technical data sheet. Having no control over the application methods and conditions or the circumstances related to its use, no other warranty, expressed or implied, statutory or otherwise is given. This limited warranty extends only to the original purchaser of the product and is not transferable or assignable. If the product fails to conform to this limited warranty, we will, at your option, furnish replacement product or refund the purchase price. This limited warranty excludes (1) labour or costs of labour for the application or removal of any product and (2) all other direct, indirect, incidental, special, or consequential damages.

© 2021 PPG Industries, Inc. All Rights Reserved. The PPG Logo is a registered trademark of PPG Industries Ohio, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, visit our web site or call 1 866 660-2220.

PPG Industries, Inc.
Architectural Coatings
One PPG Place
Pittsburgh, PA 15272
www.ppgpaints.com

PPG Architectural Coatings Canada, Inc.
1550, rue Ampère, Suite 500
Boucherville (Quebec) Canada J4B 7L4

Technical Services 1 866 660-2220
Fax: 1 800 278-8893

Architect/Specifier
1-888-PPG-IDEA