Interior Brushing Lacquer Clear Wood Finish

GENERAL DESCRIPTION

ProLuxe Interior Brushing Lacquer Clear Wood Finish is the brand to trust for an outstanding, fast drying, and easy-to-use finish for any interior wood project. Today's professionals and enthusiasts alike continue to appreciate its "forgiving nature" and resistance to brush marks, as well as, its crystal clear finish and fast drying time.

RECOMMENDED SUBSTRATES

Wood Cabinets	Wood Molding
Wood Doors	Wood Paneling
Wood Furniture	Wood Trim

FEATURES / BENEFITS

Same DEFT® Formula, New Name
Delivers the Professional Look of Fine Furniture
Enriches Finished or Unfinished Wood
Clear Finish Resists Yellowing Over Time
Fast Drying and Easy Application Makes 1-Day Finishing Possible
Self-Leveling Formula Requires No Sanding Between Coats
Won't Leave Brush Marks
Resists Alcohol, Water and Other Common Household Spills

PRODUCT INFORMATION

PLX010	Clear Gloss
PLX011	Clear Semi-Gloss
PLX017	Clear Satin

PACKAGING

Quart (946 mL)
1-Gallon (3.78 L)

PRODUCT DATA

PRODUCT TYPE:	Nitrocellulose Lacquer
SHEEN:	Gloss, 90-100 @ 60º
	Semi-Gloss 28-32 @ 60º
	Satin, 12-18 @ 60º
VOLUME SOLIDS*:	19% +/- 2%
WEIGHT SOLIDS*:	27% +/- 2%
WEIGHT/GALLON*:	7.5 lbs. (3.4 kg) +/- 0.2 lbs. (91 g)
VOC:	< 680 g/L (3.8 lbs./gal.)

*Product data calculated on product PLX010.

COVERAGE: Up to 500 sq. ft. (46.5 sq. meters) per U.S. gallon (3.78 L) depending on surface texture and porosity.

Wet Film Thickness:	3.2 mils
Wet Microns:	81
Dry Film Thickness:	0.6 mils
Dry Microns:	15

Coverage figures do not include material loss due to application or mixing.

DRYING TIME: Dry time @ 77ºF (25ºC); 50% relative humidity.

To Touch:	30 minutes
To Recoat:	2 hours
To Service:	24 hours

Drying times listed may vary depending on temperature, humidity, film build, and air movement.

CLEANUP: Clean all brushes and applicators with lacquer thinner. DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH *PROLUXE* CLEAR WOOD FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: 53ºF (11.67ºC)

LIMITATIONS OF USE

FOR WOOD SUBSTRATES ONLY. FOR INTERIOR USE ONLY. Apply when air and surface temperature is between 50°F (10°C) and 90°F (32°C).

Do not apply over varnishes, enamels or other products that dry by oxidation; it may result in lifting or wrinkling.

DO NOT USE ON FLOORS OR FOR EXTERIOR APPLICATIONS.

Interior Brushing Lacquer Clear Wood Finish

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all loose and peeling paint, dirt, grease, and any other surface contaminants. Putty all nail holes and caulk all cracks and open seams. Sand all glossy, rough, and patched surfaces. Clean and sand with 220-grit sandpaper. Remove all dust.

NEW OR BARE WOOD: Stain if desired. When applying over stained wood, ensure stain is compatible with lacquer finishes and is thoroughly dry. Sand with 220-grit sandpaper along the wood grain until smooth. Remove all dust.

PREVIOUSLY COATED WOOD: If the clean surface is in good condition, sand with 220-grit sandpaper. Remove all dust. If the finish is damaged or deteriorated, complete removal of the finish is recommended. Do not apply over varnishes, enamels or other products that dry by oxidation; it may result in lifting or wrinkling.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

APPLICATION INFORMATION

Stir well before and during use. Do not shake. DO NOT THIN. USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. Read all label and Safety Data Sheet (SDS) information prior to use. SDS are available through our web site or by calling 1-800-441-9695.

Application Equipment: For brush application only. This product must not be thinned or sprayed. Use a quality bristle brush and avoid overbrushing, since lacquers set up fast. For best results, apply thin coats and recoat in two hours. Recoat two or more times.

Brush: Natural Bristle Brush

Thinning: Do not thin.

Permissible temperatures during application:
Material: 50 to 90ºF (10 to 32ºC) Ambient: 50 to 90ºF (10 to 32ºC) Substrate: 50 to 90ºF (10 to 32ºC)

PRECAUTIONS

For warning information, please refer to the product label and SDS available at the online listing for this product at www.pittsburghpaintsco.com. Keep container tightly closed and sealed until ready for use. SDS, spill, and emergency information are available by calling 1-833-477-1553.

© 2026 The Pittsburgh Paints Co. All Rights Reserved. *Proluxe* is a registered trademark, and the *P Logo & Pittsburgh Paints* are trademarks of The Pittsburgh Paints Co. *Deft* is a registered trademark of PRC-Desoto International, Inc.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate: however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.

PITTSBURGH PAINTS CO.

The Pittsburgh Paints Company
500 Cranberry Woods Drive
Cranberry Township, PA 16066
www.pittsburghpaints.com

Technical Services
1-800-441-9695