



Premium Oil-Based Semi-Transparent Wood Finish + Sealer

GENERAL DESCRIPTION

Flood Easy Seal is a premium oil-based wood finish and sealant that provides a beautiful finish with a flawless one-coat application. Designed with a streak free performance that results in no runs and no laps, it's an easy-to-use formula to get your woodcare project done faster. Available in 8 ready-mix colors, it's recommended for decks, fences, siding and other outdoor wood surfaces.

RECOMMENDED SUBSTRATES

Wood Decks Wood Siding
Wood Fences Wood Trim

PRODUCT INFORMATION

FLDES901	Natural Cedar
FLDES902	Pecan
FLDES903	Dark Walnut
FLDES904	Mahogany
FLDES905	Natural
FLDES906	Burnt Hickory
FLDES907	Mission Brown
FLDES908	Redwood

Ready-Mixed - Do Not Tint

PACKAGING

1 - Gallon (3.78 L)
5 - Gallon (18.9 L)

Not all products are available in all sizes.

FEATURES / BENEFITS

Features

Premium Oil-Based Wood Finish + Sealer

Fortified with **PENETROL**® Additive

Penetrates Deep for a Flawless Finish

Easy One-Coat Application

Water Resistant Coating

PRODUCT DATA

PRODUCT TYPE:	Alkyd-Oil
VOLUME SOLIDS*:	69% +/- 2%
WEIGHT SOLIDS*:	73% +/- 2%
WEIGHT/GALLON*:	7.5 lbs. (3.4 kg) +/- 0.2 lbs. (91 g)
VOC:	< 275 g/L (2.3 lbs./gal.)

*Product data based on product FLDES901.

COVERAGE: On rough and weathered surfaces, 300 to 400 sq. ft. (28 to 37 sq. meters) per U.S. gallon (3.78 L). On smooth surfaces or hardwoods, 400 to 500 sq. ft. (37 to 46 sq. meters) per U.S. gallon (3.78 L). Actual coverage may vary depending on the type, age, and texture of the wood, and application method.

DRYING TIME: Normally dries in 24 hours when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Application in high humidity or in temperatures below 50°F (10°C) may prolong drying times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture.

PERMISSIBLE TEMPERATURES DURING APPLICATION:

Material:	35 to 90°F (2 to 32°C)
Ambient	35 to 120°F (2 to 49°C)
Substrate:	35 to 120°F (2 to 49°C)

CLEANUP: Clean brushes and tools with mineral spirits. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH FLOOD EASY SEAL WOOD FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.**

DISPOSAL: Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

FLASH POINT: 108°F (42°C)

Benefits

Provides a rich, subtle finish which resists cracking, flaking and peeling, and provides protection against damage from UV rays.

Provides excellent penetration.

No runs, laps or back-brushing.

Apply by brush, roller, pump-up sprayer or airless sprayer; no back-brushing required on vertical surfaces.

Protects wood from water damage.

Read Label and Safety Data Sheet prior to use. See other cautions on last page.

Premium Oil-Based Semi-Transparent Wood Finish + Sealer

GENERAL SURFACE PREPARATION

Surface must be clean and dry. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Product may be applied over wood previously coated with a weathered, semi-transparent finish in sound condition. Remove loose, peeling finish by sanding, scraping, or wire brushing. Previous finish not in sound condition should be completely removed. To ensure proper penetration, weathered, dirty, or mildewed surfaces should be cleaned with a wood cleaner prior to applying finish. After rinsing, allow wood to dry. Sand if necessary. Always sand in direction of the wood grain and remove sanding dust. Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 sec. to 2 min., depending on climate, the surface is ready for staining.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted, NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

NEW WOOD and PRESSURE TREATED LUMBER: Mill glaze must be removed by sanding and wood must pass water absorption test.

APPLICATION INFORMATION

Apply when air and surface temperatures are 35°F (2°C) to 120°F (49°C) and will remain above 35°F (2°C) for the next 24 hours. Product withstands light rain minutes after application on vertical surfaces, such as fences. For horizontal surfaces, such as decks, it is recommended to apply when no precipitation is expected for 24 hours. DO NOT THIN. Intermix containers to ensure color uniformity. Stir thoroughly and often during use. Apply to a small area and allow finish to dry to ensure acceptable appearance and penetration. Apply one thin coat with a high-quality brush, roller, or with a pump-up or airless sprayer. For horizontal surfaces such as decks, do not overapply or puddle. Brush or roll puddled areas to spread thin and ensure proper penetration and dry time. For vertical surfaces such as siding or fences, no back-brushing or rolling is necessary when applying using an airless or pump-up sprayer. If using a pump sprayer, apply to one board at a time vertically 6" to 8" from wood. Laps, runs or streaks will level out and blend into the wood.

Application Equipment: High-quality natural bristle brush, roller, pump-up sprayer or airless sprayer. Airless spray equipment must be handled with due care and in accordance with manufacturer's recommendations. High pressure injection of coatings into the skin by airless equipment may cause serious injury.

Thinning: Do Not Thin

LIMITATIONS OF USE

FOR EXTERIOR USE ONLY. FOR WOOD SUBSTRATES ONLY. While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

PRECAUTIONS

DANGER! COMBUSTIBLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. CAUSES RESPIRATORY TRACT AND EYE IRRITATION. Sanding and grinding dusts may be harmful if inhaled. Inhalation of high concentrations of vapor may affect the central nervous system. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. High vapor concentrations can cause headaches, dizziness, drowsiness and nausea and may lead to unconsciousness. Can enter lungs and cause damage. Keep away from heat and flame. Do not breathe vapor or mist. Do not swallow. Do not get on skin or clothing. Avoid contact with eyes. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. Provide fresh air ventilation during and after application and drying. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Use personal protective equipment as required. **DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH FLOOD WOOD FINISH MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATERFILLED METAL CONTAINER. Note: These warnings encompass the product series. Prior to use, read and follow product-specific SDS and label information. FIRST AID:** If swallowed, rinse mouth with water (only if the person is conscious). Call physician immediately. Do not induce vomiting unless directed to do so by medical personnel. If in eyes, rinse with water for 15 minutes. Check for and remove any contact lenses. If on skin, rinse well with water. Wash with soap and water. Get medical attention if irritation develops. If inhaled, remove to fresh air. Call physician immediately. Contains isothiazolinones. May cause allergic reaction. Keep out of the reach of children. For workplace use, an SDS is available from your retailer or by calling (412) 492-5555. EMERGENCY SPILL INFORMATION: (412) 434-4515 (U.S.).

© 2025 The Pittsburgh Paints Co. All Rights Reserved. *Flood*, *Flood and Paintbrush Design*, and *Penetrol* are registered trademarks and *Flood Easy Seal* is a trademark of The Pittsburgh Paints Co.

The Pittsburgh Paints Co. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-441-9695.



The Pittsburgh Paints Co.
400 Bertha Lamme Drive
Cranberry Township, PA 16066
www.flood.com

Technical Service
1-800-441-9695

FLDES901 6/2025